
# ACO Specification Information

# **Pipe - Support Brackets**








Support Bracket with Rubber Infill





Support Bracket with Rubber Infill and Key











## **Specifications**

### General

Used with ACO Pipe System. Used to secure ACO Pipe to the wall, floor or ceiling. Made from AISI 316L. Noncombustible. Designed for gravity piping system with maximum working pressure of 0.5 bar. Socket clamps, NBR and FPM gasket material also available upon request. Socket clamp can increase maximum operating pressure to 0.7 bar. ACO recommends checking local plumbing codes prior to installation. Manufactured to EN 1124-1 and 1124-2.

Support Bracket with Rubber Infill

Part No.	Diameter (D) in (mm)	Pipe Material	Weight Ibs
417359	1.57 (40)	316L	0.3
400529	1.97 (50)	316L	0.3
400530	2.95 (75)	316L	0.5
400531	4.33 (110)	316L	0.7
419855	4.92 (125)	316L	0.8
400532	6.30 (160)	316L	0.9
419675	7.87 (200)	316L	1
417149	9.84 (250)	316L	1.3
417224	12.40 (315)	316L	2.2

Diameter (D)

Support Bracket with Rubber Infill and Stirrup

417358 1.57 (40) 2.2 (56) 316L 0.4   400537 1.97 (50) 2.2 (5.6) 316L 0.4
<b>400537</b> 1.97 (50) 2.2 (5.6) 316L 0.4
<b>400538</b> 2.95 (75) 3.1 (80) 316L 0.6
<b>400539</b> 4.33 (110) 4.6 (116) 316L 0.9
<b>400540</b> 6.30 (160) 6.5 (166) 316L 1.2

Length (L)

Pipe

Weight

Support Bracket with Rubber Infill and Key

Part No.	Diameter (D) in (mm)	Length (L) in (mm)	Pipe Material	Weight Ibs
417361	1.57 (40)	4.7 (120)	316L	0.6
400545	1.97 (50)	4.7 (120)	316L	0.6
400546	2.95 (75)	5.2 (133)	316L	0.8
400547	4.33 (110)	5.9 (150)	316L	1.0
400548	6.30 (160)	6.9 (175)	316L	1.2

## ACO, Inc.

West Sales Office 825 W. Beechcraft Street Casa Grande, AZ 85122 Tel: (520) 421-9988 Toll-Free: (888) 490-9552 Fax: (520) 421-9899

info@acousa.com www.acousa.com www.acobuildingdrainage.us

**Part** 

@ March 2022 ACO, Inc.

All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions of use are suitable. ACO, Inc. reserves the right to change products and specifications without notice.




# 4CO Specification Information


# **Pipe - Support Brackets**





Plate for Axial Fixing





1.18" (30 mm)

Pipe Threaded Support Pole



# **Specifications**

### General

Used with ACO Pipe System. Used to secure ACO Pipe to the wall, floor or ceiling. Made from AISI 316L. Noncombustible. Designed for gravity piping system with maximum working pressure of 0.5 bar. Socket clamps, NBR and FPM gasket material also available upon request. Socket clamp can increase maximum operating pressure to 0.7 bar. ACO recommends checking local plumbing codes prior to installation. Manufactured to EN 1124-1 and 1124-2.

Plate for Axial Fixing

Part	Pipe	Weight	
No.	Material	lbs	
400561	316L	0.24	

Pipe Threaded Support Pole

rart	Diameter (D)	Length (L)	ripe	weignt
No.	in (mm)	in (mm)	Material	Ibs
400557	M8	40 (1000 mm)	Galv. Steel	0.7
400558	M8	3.5 (90 mm)	Galv. Steel	0.2
400559	M8	1.5 (40 mm)	Galv. Steel	0.2
400553	M8	40 (1000 mm)	316L	0.7
400554	M8	3.5 (90 mm)	316L	0.2
400555	M8	1.5 (40 mm)	316L	0.2

## ACO, Inc.

West Sales Office 825 W. Beechcraft Street Casa Grande, AZ 85122 Tel: (520) 421-9988 Toll-Free: (888) 490-9552 Fax: (520) 421-9899

info@acousa.com www.acousa.com www.acobuildingdrainage.us

@ March 2022 ACO, Inc.

All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions of use are suitable. ACO, Inc. reserves the right to change products and specifications without notice.

