ACO SplashLight

Installation Instructions

Product Description

ACO SplashLight contains two low-voltage battery-operated LED units which fit directly into the ACO ShowerDrain Premium channel grating. These units will illuminate once they come in contact with water and will come off approximately two minutes after the shower is turned off.

Charging ACO SplashLight

The LED unit must be fully charged before installing for the first time. Make sure the LED unit is clean and dry, then insert it into the charger.

Connect charging cord (USB-C) to wall adapter (not included). The charging process can take up to 24 hours to complete. Both units need to be charged before installation.

Technical Data

LED Units: Pre-programmed to blue lights but can be altered. Please see ACO SplashLight Programming Instructions or visit <u>www.acobd.com/splashlight</u>.



Be sure to exercise extreme caution when handling electrical devices around water.

Note

Under normal conditions of use, a fully charged module should last approximately three to six months before needing to be charged again.

For optimum performance, always keep the SplashLights fully charged to preserve lifespan.

Installing ACO SplashLight

1. Use a lifting key to remove the grate from the shower channel.



2. Remove the existing Bumper Pins from the sides of the grate.



3. Replace Bumper Pins with new ones provided with ACO SplashLight.



4. Insert SplashLight unit making sure the lights are facing toward the center of the grate and the smooth side facing down, inside the channel.



5. Carefully slide the unit into the new Bumper Pins until it locks.



ACO, Inc.

West Sales Office 825 W. Beechcraft St. Casa Grande, AZ 85122 Tel: 520-421-9988 Fax: 520-421-9899

North East Sales Office 9470 Pinecone Dr. Mentor, OH 44060 Tel: 440-639-7230 Fax: 440-639-7235

South East Sales Office 4211 Pleasant Rd. Fort Mill, SC 29708 Tel: 440-639-7230 Fax: 803-802-1063

info@acousa.com www.acobd.com

© December 2021 ACO, Inc.

All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions of use are suitable. ACO, Inc. reserves the right to change products and specifications without notice. Print #SD703

6. Place the grating back into the channel and press down gently until whole unit becomes flush.



Maintenance

Before charging the LED units, thouroughly clean and fully dry the entire surface prior to inserting them into the charger.

The supplied charger is to be used ONLY with the ACO SplashLight LED units. Use of this charger with any other rechargeable batteries may result in severe damage to the unit.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.





ACO. creating the future of drainage