


ACO ENVIRONMENT Jun 11


Oleopator Inspection & Sampling Chamber













ACO Specification Information

ACO ENVIRONMENTAL

Oleopator Inspection & Sampling Chamber

Unit Height (inches)	Unit Dia (inches)	Pipe Size (inches)	Manhole Cover Dia (inches)	Weight lbs
112.26	45.37	To suit site requirements	24.0	365.0

Specifications

General

The inspection chamber and sampling chamber element of the bypass separator system shall be ACO Environment Oleopator Inspection & Sampling Chamber as manufactured by ACO Polymer Products, Inc. or equal approved.

Materials

The separator body shall be manufactured from fiberglass, with minimum properties as follows:

Compressive strength: 24,400 psi Flexural strength: 9,943 psi Water absorption 0.33% Frost proof Salt proof

Dilute acid and alkali resistant

The nominal body diameter shall be 42" (1066mm) with overall width of 45.37" (1152mm). Units shall be manufactured with a wall thickness of at least 0.125" (3mm). Each unit will feature an extension collar to provide adjustable overall height from 73.29" (1861mm) up to 112.26" (2851mm) that can but cut to size on site to suit local requirements. The body shall be manufactured with inlet and outlet pipes custom sized and at custom inlet depth to suit site requirements.


Access Cover

A solid cast iron cover of 24.00" (600mm) diameter and frame are supplied to provide access into the sludge chamber for maintenance. Complies with AASHTO M306-05.

Installation

The separator system shall be installed in accordance with the manufacturer's installation instructions and recommendations.

The Oleopator Inspection Chamber & Sampling Unit are part of a 4-unit bypass separator system. For information on the additional units please contact ACO.



ACO Polymer Products, Inc.

East Sales Office P.O. Box 245

Chardon, OH 44024 Tel: (440) 285-7000 Toll free: (800) 543-4764 Fax: (440) 285-7005

West Sales Office

P.O. Box 12067 Casa Grande, AZ 85230 Tel: (520) 421-9988 Toll Free: (888) 490-9552 Fax: (520) 421-9899

Electronic Contact:

info@acousa.com www.acousa.com

