## 8" width - ductile iron slotted grate









## **Product Features**

- Certified to EN 1433 Load Class F 200,000 lbs 4,182 psi
- Uses 'PowerLok' boltless locking system
- Suitable for use with \$200K and H200SK channels
- Manufactured from ductile iron to ASTM A 536-84 Grade 304 65-45-12
- Anti-Shunt lugs



## **Specifications**

#### General

The surface drainage system shall be ACO PowerDrain or SlabDrain, complete with ACO ductile iron slotted grate with 'PowerLok' locking as manufactured by ACO, Inc. or similar approved.

#### Material

The covers shall be manufactured from ductile iron and have **minimum** properties as follows:

- Independently certified to meet Load Class F to EN 1433 - 200,000 lbs - 4,182 psi
- Ductile iron to ASTM 536-84 Grade 65-45-12
- Intake area of 450 sq. cm per ½ meter of grate

The overall width of 9.35" (238mm) and overall length of 19.68" (500mm). Slots measure at a maximum of 0.75" (19mm).

#### Grate

Grate is slotted ductile iron. Ductile iron ASTM 536-84 - Grate 65-45-12. After removal of grates there shall be uninterrupted access to the trench to aid maintenance. Grates can be used for PowerDrain or SlabDrain.

#### Installation

The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

\* delete as appropriate



ACO Specificat


# 8" width - ductile iron slotted grate

## Plan view










### **Side elevation**

Informa


ACO Specifica





Description	Part No.	Length inches <i>(mm)</i>	Width inches (mm)	Weight lbs.
PowerLok grate SK2 ductile iron longitudinal grate - Cl E	02449	19.68 (500)	9.35 (238)	26.4

## PowerLok locking mechanism



ACO PowerLok is a patented boltless locking system. Grates are removed and replaced with minimum time and effort for ease of maintenance.

Lugs on the rail opposite the PowerLok device slots into recesses in the grate. The PowerLok device is used to engage the lug on the rail at two locations per grate to 'lock' the grate to the channel.

#### ACO, Inc. **Northeast Sales Office** 9470 Pinecone Drive

Mentor, Ohio 44060 Tel: (440) 639-7230 Toll free: (800) 543-4764 Fax: (440) 639-7235

## **West Sales Office**

825 W. Beechcraft St. Casa Grande, AZ 85122 Tel: (520) 421-9988 Toll Free: (888) 490-9552 Fax: (520) 421-9899

## **Southeast Sales Office**

4211 Pleasant Road Fort Mill, SC 29708 Toll free: (800) 543-4764 Fax: (803) 802-1063

### Follow us on



**Electronic Contact:** info@ACODrain.us

www.ACODrain.us



© September 2018, ACO, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO, Inc. reserves the right to change the product and specifications without notice.