Product Features

- Certified to EN 1433 Load Class E 135,000 lbs 2,788 psi
- Uses 'DrainLok' boltless locking system
- Manufactured from ductile iron
- Complies with ADA American Disabilities Act of 1990 Section 4.5.4
- Complies with ASME: A112.6.3 2001: Section 7.12 Heel Resistant Strainers and Grates
- Bicycle Tire Penetration Resistant to AS3996-2006

Specifications

General

The surface drainage system shall be ACO Utility Duct DK100 complete with Type 456D ductile iron solid cover as manufactured by ACO Polymer Products, Inc. or similar approved.

Materials

The covers shall be manufactured from ductile iron and have *minimum* properties as follows:

- Independently certified to meet Load Class E to EN 1433 - 135,000 lbs - 2,788 psi
- Ductile iron to ASTM A536-84-Grade 65-45-12

The overall width of 4.84" and overall length of 19.69".

Installation

The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

*delete as appropriate


 \bigoplus




ACO DRAIN Type 456D Solid ductile iron grate


Plan view






Side elevation





Description	Part No.	Length inches <i>(mm)</i>	Width inches <i>(mm)</i>	Weight Ibs.
Type 456D Solid ductile iron grate	12672	19.69 (<i>500</i>)	4.84 (123)	12.53

'DrainLok' locking mechanism



ACO Polymer Products, Inc.

Northeast Sales Office 9470 Pinecone Drive Mentor, OH 44060 Tel: (440) 639-7230 Toll free: (800) 543-4764 Fax: (440) 639-7235 West Sales Office 825 W. Beechcraft St. Casa Grande, AZ 85122 Tel: (520) 421-9988 Toll Free: (888) 490-9552 Fax: (520) 421-9899 **Southeast Sales Office** 4211 Pleasant Road Fort Mill, SC 29708 Toll free: (800) 543-4764 Fax: (803) 802-1063



Electronic Contact: info@ACODrain.us www.ACODrain.us



© September 2016 ACO Polymer Products, Inc. This information is believed to be accurate but it is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for his own use. ACO Polymer Products Inc. reserves the right to change the product and specifications without notice. Reorder# DL149

September 2016

www.ACODrain.us